§58.129

Vacuum chambers located on the pasteurized side of the unit shall be isolated by means of a vacuum breaker and a positive activated check valve on the product inlet side and a vacuum breaker and a positive activated check valve on the discharge side. If direct steam is used, it should also be equipped with a ratio controller to regulate the composition when applicable to the finished product. Only steam which meets the requirements for culinary steam shall be used. The incoming steam supply shall be regulated by an automatic solenoid valve which will cut off the steam supply in the event the flow diversion valve of the pasteurizer is not in the forward flow position. Condensers when used shall be equipped with a water level control and an automatic safety shutoff valve.

PERSONNEL, CLEANLINESS AND HEALTH

§58.129 Cleanliness.

All employees shall wash their hands before beginning work and upon returning to work after using toilet facilities, eating, smoking or otherwise soiling their hands. They shall keep their hands clean and follow good hygienic practices while on duty. Expectorating or use of tobacco in any form shall be prohibited in each room and compartment where any milk, dairy products, or supplies are prepared, stored or otherwise handled. Clean white or light-colored washable or disposable outer garments and caps (paper caps, hard hats, or hair nets acceptable) shall be worn to adequately protect the hair and beards when grown by all persons engaged in receiving, testing, processing milk, manufacturing, packaging or handling dairy products.

§ 58.130 Health.

No person afflicted with a communicable disease shall be permitted in any room or compartment where milk and dairy products are prepared, manufactured or otherwise handled. No person who has a discharging or infected wound, sore or lesion on hands, arms or other exposed portion of the body shall work in any dairy processing rooms or in any capacity resulting in contact with milk, or dairy products. Each employee whose work brings him in con-

tact with the processing or handling of dairy products, containers or equipment should have a medical and physical examination by a registered physician or by the local department of health at the time of employment. An employee returning to work following illness from a communicable disease shall have a certificate from the attending physician to establish proof of complete recovery.

PROTECTION AND TRANSPORT OF RAW MILK AND CREAM

§58.131 Equipment and facilities.

(a)(1) Milk cans. Cans used in transporting milk from dairy farm to plant shall be of such construction (preferably seamless with umbrella lids) as to be easily cleaned, and shall be inspected, repaired, and replaced as necessary to exclude substantially the use of cans and lids with open seams, cracks, rust, milkstone, or any unsanitary condition. Adequate provisions should be made so that milk in cans will be cooled immediately after milking to 50 °F. or lower unless delivered to the plant within two hours after milking.

(2) Farm bulk tanks. Farm bulk tanks shall comply with 3-A Sanitary Farm Cooling and Holding Tanks or 3-A Sanitary Standards for Farm Cooling and Holding Tanks or 3-A Sanitary Standards for Farm Milk Storage Tanks as applicable. They shall be installed in a milk house in accordance with the requirements of the regulatory agency in jurisdiction. The bulk cooling tanks shall be designed and equipped with refrigeration to permit the cooling of the milk to 40 °F. or lower within two hours after milking, and maintain it at 45 °F. or below until picked up.

(b)(1) Receiving stations. Receiving stations shall comply with the applicable sections of this subpart covering premises, buildings, facilities, equipment, utensils, personnel, cleanliness and health.

(2) Transfer stations. Transfer stations shall comply with the applicable sections of this subpart covering premises, floors, lighting, water supply, handwashing facilities, disposal of wastes,